


## **Y**-Rain<sup>®</sup> Throttling Valve





## **Applications**

- This valve is primarily used for manually throttling downstream pressure down.
- This valve is a reliable throttle valve in place of an expensive brass valve.
- The 3" brass valve may be used for 3" pipe as well as 4" pipe using a set of 4" x 3" reducers when the application is pressure reduction.
- The two side windows help to set and mark the downstream pressure setting location for future reference.

## **Features & Benefits**

- Multi-turn, linear motion throttle valve for working pressure up to 90 psi (6 bars).
- Its slow closing feature helps to prevent water hammering.
- Steel rod inserted through full length of shaft during injection molding of shaft made of reinforced Nylon that gives excellent strength.
- Float body inside profile is matched by CNC machine for smooth operation and keeping the leakage under permissible limit during complete shut off.
- Dowel pin inserted in the shaft to prevent extra travel of float which do not transfer load on during extra tightening by farmers. This prevents breakage of cap.
- During assembly of throttle valve, two lock pins are inserted to avoid any slippage or loosening of threads of throttle valve cap.
- All parts coming in contact with water are Chemical/Corrosion resistant and also the colors are UV stabilized making it ideally suited for fertigation and chemigation (please consult material section on this page and strength of fertilizers/chemicals used for suitability).

Specification of Material													
PART NO.	PART NAME	MATERIAL	QTY.		PART NO.	PART NAME	MATERIAL	QTY					
1	Body	Reinforced PP	1		9	Bottom Gasket	NBR	1					
2	Flange	Reinforced PA	1		10	Sleeve Gasket	NBR	1					
3	Disc	Reinforced PA	1		11	Handle Screw	SS-304	1					
4	Handle	Reinforced PA	1		12	Tefflon Seal Big	Teflon	1					
5	Cylinder	Reinforced PP	1		13	Tefflon Seal Small	Teflon	1					
6	PC Housing	Polycarbonate	1		14	Housing Gasket	NBR	2					
7	shaft	Reinforced PA+MS	1		15	Locking Pin	SS-304	2					
8	Shaft O-ring	NBR	2		16	Dowel Pin(4*30)SS	SS-304	2					

Dimensions											
Nom	NPT	d	dk	Е	L	Н					
Size	Thd./in										
2"	11.5	2.56"	1.89"	4.61"	5.12"	10.83"					
3"	8	3.66"	2.91"	4.61"	7.17"	15.35"					